

1A,50-1000V Fast Recovery Rectifiers

Features

- Low leakage current
- Low forward voltage drop
- Glass passivated chip junction
- For general purpose applications
- Moisture sensitivity: level 1, per J-STD-020
- For fast switching and low logic level applications
- High temperature soldering guaranteed: 260°C/10 seconds



DO-41(DO-204AL)

Applications

- Small battery charger, Power supplies

Maximum Ratings & Electrical Characteristics (T_A=25°C unless otherwise noted)

| Parameter | Symbol | RGP10A | RGP10B | RGP10D | RGP10G | RGP10J | RGP10K | RGP10M | Unit |
|--|--------------------|-------------|--------|--------|--------|--------|--------|--------|------|
| Maximum repetitive peak reverse voltage | V _{RRM} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V |
| Maximum RMS voltage | V _{RMS} | 35 | 70 | 140 | 280 | 420 | 560 | 700 | V |
| Maximum DC blocking voltage | V _{DC} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V |
| Maximum average forward rectified current | I _{F(AV)} | 1 | | | | | | | A |
| Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load per diode | I _{FSM} | 30 | | | | | | | A |
| Operating junction temperature range | T _J | -55 to +150 | | | | | | | °C |
| Storage temperature range | T _{STG} | -55 to +150 | | | | | | | °C |

Thermal-Mechanical Specifications (T_A=25°C unless otherwise noted)

| Parameter | Symbol | Typ | Unit |
|---|------------------|-----|--------|
| Thermal Resistance, Junction to Ambient | R _{θJA} | 52 | °C / W |
| Thermal Resistance, Junction to Case | R _{θJC} | 24 | °C / W |
| Thermal Resistance, Junction to Lead | R _{θJL} | 13 | °C / W |



RGP10A thru RGP10M

GOOD-ARK Electronics

Electrical Specifications (T_A=25°C unless otherwise noted)

| Parameter | Symbol | Test Conditions | RGP10A | RGP10B | RGP10D | RGP10G | RGP10J | RGP10K | RGP10M | Unit | |
|---|-----------------|--|--------|--------|--------|--------|--------|--------|--------|------|----|
| Forward Drop Voltage | V _F | I _F =1A | 1.30 | | | | | | | V | |
| Reverse leakage current @V _R | I _R | T _J =25°C | 5 | | | | | | | uA | |
| | | T _J =125°C | 100 | | | | | | | | |
| Typical junction capacitance | C _J | 4.0 V 1 MHz | 12 | | | | | | | pF | |
| Maximum reverse recovery time | t _{rr} | I _F =0.5A, I _R =1.0A, I _{RR} =0.25A | 150 | | | | 250 | | 500 | | nS |

Note:

- Valid provided that leads at a distance of 9.5 mm from case are kept at ambient temperature.

Ratings and Characteristics Curves

($T_A = 25^\circ\text{C}$ unless otherwise noted)









FIG.5 - REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM



NOTES: 1. Rise Time=7ns max. Input Impedance=1 megohm 22pf
2. Rise Time=10ns max. Source Impedance=50 ohms




SET TIME BASE FOR 5/10ns/cm

Package Outline Dimensions

in inches (millimeters)

DO-41(DO-204AL)



Dimensions in inches and (millimeters)

Revision History

| Document Version | Date of release | Description of changes |
|------------------|-----------------|------------------------|
| Rev.A | 2021.06.01 | Released Datasheet |
| Rev.B | 2023.11.13 | Modify document format |

Disclaimers

These materials are intended as a reference to assist our customers in the selection of the Suzhou Good-Ark product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Suzhou Good-Ark Electronics Co., Ltd. or a third party.

Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.

All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Suzhou Good-Ark Electronics Co., Ltd. without notice due to product improvements or other reasons. It is therefore recommended that customers contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized Suzhou Good-Ark Electronics Co., Ltd. for the latest product information before purchasing a product listed herein. The information described here may contain technical inaccuracies or typographical errors. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors. Please also pay attention to information published by Suzhou Good-Ark Electronics Co., Ltd. by various means, including our website home page.

(<http://www.goodark.com>)

When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, Please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.

The prior written approval of Suzhou Good-Ark Electronics Co., Ltd. is necessary to reprint or reproduce in whole or in part these materials.

Please contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized distributor for further details on these materials or the products contained herein.